DOCKET NO.: MSFT-0580/167506.02

Application No.: 09/900,059

Office Action Dated: February 23, 2004

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

(original) A method for automatically classifying consonance of audio data, comprising: 1.

applying audio data to a peak detection process;

detecting the location of at least one prominent peak represented by the audio data in the

frequency spectrum and determining the energy of the at least one prominent peak;

storing the location of the at least one prominent peak and the energy of the at least one

prominent peak into at least one output matrix;

applying the data stored in said at least one output matrix to critical band masking

filtering;

applying the data stored in said at least one output matrix to a peak continuation process;

and

applying the data stored in said at least one output matrix to an intervals calculation

process where the frequency of ratios between peaks are stored into an output vector for the

audio data being classified.

2. (original) A method according to claim 1, wherein the audio data is divided into frames,

and the method is performed frame by frame.

3. (original) A method according to claim 2, wherein the frame by frame approach includes

bin differencing to calculate frame derivatives to facilitate the detection of peaks.

Page 2 of 18

DOCKET NO.: MSFT-0580/167506.02 PATENT

Application No.: 09/900,059

Office Action Dated: February 23, 2004

4. (original) A method according to claim 2, wherein the number of peaks detected in said

application of the peak detection process is limited by a pre-defined parameter.

5. (original) A method according to claim 1, further comprising performing Nth order

interpolation on the location of the at least one prominent peak and the energy of the at least one

prominent peak to increase precision of the location and energy values for the peak.

6. (original) A method according to claim 1, further comprising applying the output vector

to a classification stage which determines at least one of (1) at least one consonance value and

(2) at least one consonance class that describes the audio data.

7. (original) A method according to claim 1, where the frequency of ratios between peaks

are stored into an output vector that is 1 x 24.

8. (original) A method according to claim 2, wherein the peak continuation process keeps

track of peaks that last more than a predetermined number of frames

9. (original) A method according to claim 8, wherein the peak continuation process fills in

a peak when the peak is missed in a previous frame.

Page 3 of 18

DOCKET NO.: MSFT-0580/167506.02

Application No.: 09/900,059

Office Action Dated: February 23, 2004

(original) A method according to claim 1, wherein said critical band masking filtering

PATENT

removes a peak that is masked by surrounding peaks with more energy

(original) A method according to claim 10, wherein said critical band masking filtering 11.

removes a peak when at least one of a lower frequency peak and a higher frequency peak have

greater energy.

12. (original) A method according to claim 10, wherein said critical band masking filters are

scalable so that the amount of masking is scalable.

13. (original) A method according to claim 1, wherein said storing includes providing an

output of the peak detection and interpolation stage in two matrices, one holding the location of

the at least one prominent peak, and the second holding the respective energy of the at least one

prominent peak.

(original) A method according to claim 1, wherein the audio data is formatted according 14.

to pulse code modulated format.

15. (original) A method according to claim 14, wherein the audio data is previously in a

format other than pulse code modulated format, and the method further comprises converting the

audio data to pulse code modulated format from the other format.

DOCKET NO.: MSFT-0580/167506.02

Application No.: 09/900,059

Office Action Dated: February 23, 2004

(original) The method of claim 1, further comprising converting the input audio data 16. from the time domain to the frequency domain.

17. (original) A method according to claim 16, wherein said converting of the input audio

data signal from the time domain to the frequency domain includes performing a fast fourier

transform on the audio data.

18. (currently amended) A computer readable medium bearing computer executable

instructions for: carrying out the method of claim 1.

applying audio data to a peak detection process;

detecting the location of at least one prominent peak represented by the audio data in the

frequency spectrum and determining the energy of the at least one prominent peak;

storing the location of the at least one prominent peak and the energy of the at least one

prominent peak into at least one output matrix;

applying the data stored in said at least one output matrix to critical band masking

filtering;

applying the data stored in said at least one output matrix to a peak continuation process;

and

applying the data stored in said at least one output matrix to an intervals calculation

process where the frequency of ratios between peaks are stored into an output vector for the

audio data being classified.

DOCKET NO.: MSFT-0580/167506.02

Application No.: 09/900,059

Office Action Dated: February 23, 2004

19. (currently amended) A modulated data signal carrying computer executable instructions for: performing the method of claim 1.

applying audio data to a peak detection process;

detecting the location of at least one prominent peak represented by the audio data in the frequency spectrum and determining the energy of the at least one prominent peak;

storing the location of the at least one prominent peak and the energy of the at least one prominent peak into at least one output matrix;

applying the data stored in said at least one output matrix to critical band masking filtering:

applying the data stored in said at least one output matrix to a peak continuation process; and

applying the data stored in said at least one output matrix to an intervals calculation process where the frequency of ratios between peaks are stored into an output vector for the audio data being classified.

20. (currently amended) At least one computing device comprising means one or more subsystems for: performing the method of claim 1.

applying audio data to a peak detection process;

detecting the location of at least one prominent peak represented by the audio data in the frequency spectrum and determining the energy of the at least one prominent peak;

storing the location of the at least one prominent peak and the energy of the at least one prominent peak into at least one output matrix;

DOCKET NO.: MSFT-0580/167506.02

Application No.: 09/900,059

Office Action Dated: February 23, 2004

applying the data stored in said at least one output matrix to critical band masking filtering:

applying the data stored in said at least one output matrix to a peak continuation process; and

applying the data stored in said at least one output matrix to an intervals calculation process where the frequency of ratios between peaks are stored into an output vector for the audio data being classified.

21. (original) A method of classifying data according to consonance properties of the data, comprising:

assigning to each media entity of a plurality of media entities in a data set to at least one consonance class:

processing each media entity of said data set to extract at least one consonance characteristic based on digital signal processing of each media entity;

generating a plurality of consonance vectors for said plurality of media entities, wherein each consonance vector includes said at least one consonance class and at least one consonance characteristic based on digital signal processing; and

forming a classification chain based upon said plurality of feature vectors.

22. (original) A method according to claim 21, further comprising:

processing an unclassified media entity to extract at least one consonance characteristic based on digital signal processing of the unclassified media entity;

DOCKET NO.: MSFT-0580/167506.02

Application No.: 09/900,059

Office Action Dated: February 23, 2004

generating a vector for the unclassified media entity including said at least one digital signal processing consonance characteristic;

presenting the vector for the unclassified media entity to the classification chain; and classifying the unclassified entry with an estimate of the consonance class by calculating the representative consonance class of the subset of the plurality of vectors of the classification chain located in the neighborhood of the vector for the unclassified entity.

- 23. (original) A method according to claim 22, further including calculating a neighborhood distance that defines a distance within which two vectors in the classification chain space are in the same neighborhood for purposes of being in the same consonance class.
- 24. (original) A method according to claim 22, wherein said classifying of the unclassified entry includes classifying the unclassified entry with a median consonance class represented by the neighborhood.
- 25. (original) A method according to claim 22, wherein said consonance class is described by a numerical value and said classifying of the unclassified entry includes classifying the unclassified entry with a mean of numerical consonance values found in the neighborhood.
- (original) A method according to claim 22, wherein said classifying includes returning at 26. least one number indicating the level of confidence of the consonance class estimate.

DOCKET NO.: MSFT-0580/167506.02

Application No.: 09/900,059

Office Action Dated: February 23, 2004

27. (currently amended) A computer readable medium bearing computer executable instructions for: earrying out the method of claim 21.

assigning to each media entity of a plurality of media entities in a data set to at least one consonance class;

processing each media entity of said data set to extract at least one consonance characteristic based on digital signal processing of each media entity;

generating a plurality of consonance vectors for said plurality of media entities, wherein each consonance vector includes said at least one consonance class and at least one consonance characteristic based on digital signal processing; and

forming a classification chain based upon said plurality of feature vectors.

28. (currently amended) A modulated data signal carrying computer executable instructions for: performing the method of claim 21.

assigning to each media entity of a plurality of media entities in a data set to at least one consonance class;

processing each media entity of said data set to extract at least one consonance characteristic based on digital signal processing of each media entity;

generating a plurality of consonance vectors for said plurality of media entities, wherein each consonance vector includes said at least one consonance class and at least one consonance characteristic based on digital signal processing; and

forming a classification chain based upon said plurality of feature vectors.

DOCKET NO.: MSFT-0580/167506.02

Application No.: 09/900,059

Office Action Dated: February 23, 2004

29. (currently amended) At least one computing device comprising means for: performing the method of claim 21.

assigning to each media entity of a plurality of media entities in a data set to at least one consonance class;

processing each media entity of said data set to extract at least one consonance characteristic based on digital signal processing of each media entity;

generating a plurality of consonance vectors for said plurality of media entities, wherein each consonance vector includes said at least one consonance class and at least one consonance characteristic based on digital signal processing; and

forming a classification chain based upon said plurality of feature vectors.

30. (original) A computing system, comprising:

a computing device including:

a classification chain data structure stored thereon having a plurality of classification vectors, wherein each vector includes data representative of a consonance class as classified by humans and consonance characteristics as determined by digital signal processing; and

processing means for comparing an unclassified media entity to the classification chain data structure to determine an estimate of the consonance class of the unclassified media entity.

31. (original) A computing system according to claim 30, wherein said determining of an estimate of the consonance class includes returning at least one number indicating the level of confidence of the consonance class assignment.

DOCKET NO.: MSFT-0580/167506.02

Application No.: 09/900,059

Office Action Dated: February 23, 2004

32. (original) A method according to claim 31, wherein the performance level of the classification chain improves over time due to the examination of unclassified media entities that have a low confidence level associated with the consonance class assignment.

33. (original) A classification chain data structure utilized in connection with the classification of consonance of new unclassified media entities, comprising:

a plurality of classification vectors, wherein each vector includes:

consonance data as classified by humans; and

consonance data determined by digital signal processing techniques.

[Remainder of Page Intentionally Left Blank]